

# Homework 5 in Advanced Methods of Cryptography

Prof. Dr. Rudolf Mathar, Michael Reyer, Henning Maier

29.11.2013

**Exercise 12.** A block cipher is a cryptosystem where both plaintext and ciphertext space are the set  $\mathcal{A}^n$  of words of length  $n$  over an alphabet  $\mathcal{A}$ .

- (a) Show that the encryption functions of block ciphers are permutations.
- (b) How many different block ciphers exist if  $\mathcal{A} = \{0, 1\}$  and the block length is  $n = 6$ ?

**Exercise 13.** Consider the following AES-128 key given in hexadecimal notation:

$$K = 2D\ 61\ 72\ 69\ 65\ 00\ 76\ 61\ 6E\ 00\ 43\ 6C\ 65\ 65\ 66\ 66$$

- (a) What is the round key  $K_0$ ?
- (b) What are the first 4 bytes of round key  $K_1$ ?

**Exercise 14.** The step `MixColumns` of the AES scheme is given by  $\mathbf{r} = \mathbf{T}\mathbf{c}$  with input  $\mathbf{c} = (c_0, c_1, c_2, c_3)' \in \mathbb{F}_{2^8}^4$ , output  $\mathbf{r} = (r_0, r_1, r_2, r_3)' \in \mathbb{F}_{2^8}^4$ , and the circulant matrix

$$\mathbf{T} = \begin{pmatrix} x & (x+1) & 1 & 1 \\ 1 & x & (x+1) & 1 \\ 1 & 1 & x & (x+1) \\ (x+1) & 1 & 1 & x \end{pmatrix} \in \mathbb{F}_{2^8}^{4 \times 4},$$

for the polynomial field  $\mathbb{F}_{2^8} = \mathbb{F}_2[X]/(x^8 + x^4 + x^3 + x + 1)\mathbb{F}_2[X]$ .

Show  $(c_3u^3 + c_2u^2 + c_1u + c_0)((x+1)u^3 + u^2 + u + x) \bmod (u^4 + 1) = r_3u^3 + r_2u^2 + r_1u + r_0$ .